

FLAMMABILITY TEST CERTIFICATE - 93156

COMPANY DETAILS: MODELLI FABRICS

DERWENT BRIDGE HOUSE COCKERMOUTH CA13 0HW

CONTACT NAME(S): TIM KENNEDY
TEL: 01949851116

EMAIL: tim@modellifabrics.com

 DATE RECEIVED:
 05/10/2022

 DATE TESTED:
 11/10/2022

 DATE ISSUED:
 11/10/2022

PO NUMBER:

SAMPLE DESCRIPTION: **OLYMPIA COLOUR: NOT STATED QUALITY/BATCH REF: NOT STATED** MODEL REF: NOT STATED **COMPOSITION:** 100% POLYESTER SAMPLE END USE: **NOT STATED MANUFACTURER: NOT STATED** SUPPLIER/BUYER: **NOT STATED**

TEST METHOD(S):

BS 5852:2006 Clause 11 – Method of test for the ignitibility of upholstered composites ignition source 5.

PRE-TREATMENT:

Water Soak procedure in accordance with Annex E of BS 5852:2006.

CONDITIONING:

The sample was conditioned for 72 hrs in ambient conditions for at least 24 hrs in a specified atmosphere at $23 \pm 2^{\circ}$ C and $50 \pm 5\%$ r h.

Authorised By:

Zeb Alam Operations Director Mark Jones Quality Manager Karen Brooks
Managing Director

Please note: The uncertainty of measurement is taken into account when stating conformance to the specification. The measured value(s) marked* are compared with the 'acceptance interval" which is determined by reducing the specification limits by the expanded test uncertainty Uk=2 (approximately 95% confidence interval). Results outside these limits are declared as 'fail'. All test results issued on this report refer only to the item under test as supplied by the customer. This test report shall not be duplicated. Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN T: 0161 50 50 650 E: technical@ifs-labs.com





FLAMMABILITY TEST CERTIFICATE – 93156

TEST RESULTS:

"The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use."

TEST RESULTS:

TEST CRITERIA – BS 5852:2006 Source 5	INITIAL TEST	REPEAT TEST
Flaming Ceased:	04.37	04.21
PROGRESSIVE SMOULDERING CRITERIA (4.1)		
FILLING MATERIAL USED:	GB33M	GB33M
b) Detectable amounts of smoke, heat or glowing 60 mins after crib ignition?	NO	NO
c) Displays unsafe escalating combustion, requires to be forcibly extinguished?	NO	NO
d) Smouldering consumed the test specimen within the duration of the test?	NO	NO
e) Smoulder to the extremities i.e. upper or lower margins, either side or to its full thickness?	NO	NO
f) On final inspection, any evidence of charring more than 100 mm in any direction (apart from upwards) from the original nearest position?	NO	NO
FLAMING CRITERIA (4.2)		
b) Flaming continued for more than 10 minutes after the ignition of the crib?c) Displays unsafe escalating combustion, requires to be forcibly	NO	NO
extinguished?	NO	NO
d) Flaming and/or smouldering consumed the test specimen within the duration of the test?e) Flame front reaches the lower margin, either side or passes through	NO	NO
the full thickness?	NO	NO
TEST RESULTS	PASS	PASS

CONCLUSION:

The sample supplied meets the test criteria of BS 5852:2006 Clause 11

Please note: The uncertainty of measurement is taken into account when stating conformance to the specification. The measured value(s) marked* are compared with the 'acceptance interval" which is determined by reducing the specification limits by the expanded test uncertainty Uk=2 (approximately 95% confidence interval). Results outside these limits are declared as 'fail'. All test results issued on this report refer only to the item under test as supplied by the customer. This test report shall not be duplicated. Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN T: 0161 50 50 650 E: technical@ifs-labs.com

