# **TECHNICAL REPORT**



Maxwell Road Stevenage Hertfordshire SG1 2EW

T: +44(0) 1438 777 700 info@fira.co.uk

www.fira.co.uk

Modelli Fabrics Our Ref: FL-19470-S1A\*

Derwent Bridge House Date: 11 August 2021

Gote Road Delivery Date: 27 July 2021

Cockermouth Test Dates: 30 July – 06 August 2021

Cumbria CA13 0HW

For the attention of Tim Kennedy

#### SAMPLE(S) FOR TEST:

One, Fabric - Ref: Passione 2.0 4193

 FR ID Number
 4193

 Audit No.
 C194083

 Quality
 Passione 2.0

 Batch
 210401

Colour 4193 Puppy Breath Piece No. AN435562

Note: The above descriptions are as supplied by the client and have not been verified by FIRA International who can take no responsibility for the accuracy of the description.

### TEST REQUIREMENTS: RESULT:

 Schedule 4 Part I (based on BS 5852: 1979 Part 1)
 Pass - P0

 Schedule 5 Part I (based on BS 5852: 1979 Part 1)
 Pass - P1

The material was subjected to the water soak procedure and line dried as detailed in The Furniture and Furnishings (Fire) (Safety) Regulations 1988, amended 1989, 1993 and 2010.

FIRA International is a UKAS TESTING Laboratory No. 0174

Tests marked "Not UKAS Accredited" in this Report are not included in the UKAS Accreditation Schedule for our laboratory.

Technical report references marked \* indicate this report is supplementary to the previous report with the same reference.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

This Report relates to the sample(s) submitted for test and no others. Additions, deletions or alterations are not permitted.

Test reports are given to the client in confidence, and may only be reproduced in whole or in part with written permission from FIRA International Limited. Note that the words "tested by FIRA International" may be used in subsequent publicity for the product; "approved" must not be used.

Tests are carried out on the understanding that neither FIRA International Limited nor its officers can accept any legal responsibility for information or advice given or opinions expressed whether in response to specific enquiries or otherwise. This Report is given subject to the Terms of Business of FIRA International Limited which are available at <a href="https://www.fira.co.uk/images/FIRA-International-Limited-Standard-Terms-of-Business-2018.pdf">https://www.fira.co.uk/images/FIRA-International-Limited-Standard-Terms-of-Business-2018.pdf</a>



# TECHNICAL REPORT

## **DESCRIPTION**

**Enquiry No:** FL-19470-S1A\*

Item: One, Fabric - Ref: Passione 4193

Supplied by: Modelli Fabrics

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

## FURNITURE AND FURNISHINGS (FIRE) (SAFETY) REGULATIONS 1988 - AMENDED 1989, 1993 AND 2010 SCHEDULE 4 PART 1 MODIFICATION TO BS 5852: PART 1 THE CIGARETTE TEST

Initial Inspection: Condition as new.

Conditioning: ≥3 days at indoor ambient conditions and ≥16 hours at 20±5°C & 50±20% rh.

Filling Material: A conventional urethane foam of nominal density 20-22kgm3 Ref: VP45, and an 85g thermally bonded polyester

fibre wrap.

Test Procedure: As defined in Schedule 4 Part 1 of the above regulations.

Test Conditions: The test was conducted within the required conditions of 15-30°C & 20-70%rh.

#### **RESULTS**

Source No.	Application No.	Smoke/ Smoulder	Result - Ignition/ Non-Ignition
0	1	15min 21sec	PASS N/I
	2	15min 46sec	PASS N/I

# **COMMENTS**

SCHEDULE 4 PART 1 MODIFICATION TO BS 5852: PART 1 THE CIGARETTE TEST	APP 1.	APP 2.
Both cigarettes were fully consumed within the stipulated 1 hour time period, however the cover and filling assembly continued to smoulder for greater than the stipulated 60min time period.	NO - PASS N/I	NO - PASS N/I
Progressive smouldering was established, the rate of smoulder was rapid, and the test was terminated before the stipulated time period.	NO - PASS N/I	NO - PASS N/I
Flames occurred though progressive smouldering, therefore the test was terminated before the stipulated 60min time period as it was deemed unsafe to continue.	NO - PASS N/I	NO - PASS N/I

### CONCLUSION

This fabric sample Ref: 4358 FR Ombra, passes the test specified in Schedule 4 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations 1988 - Amended 1989, 1993 and 2010.





# TECHNICAL REPORT

#### **DESCRIPTION**

Enquiry No: FL-19470-S1A\*

Item: One, Fabric – Ref: Passione 4193

Supplied by: Modelli Fabrics

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

# FURNITURE AND FURNISHINGS (FIRE) (SAFETY) REGULATIONS 1988 - AMENDED 1989, 1993 AND 2010 SCHEDULE 5 PART 1 THE MATCH TEST (BASED ON BS 5852: 1979 PART 1)

Initial Inspection: Condition as new.

Conditioning: ≥3 days at indoor ambient conditions and ≥16 hours at 20±5°C & 50±20% rh.

**Test Procedure:** As defined in Schedule 5 Part 1 of the above regulations using specified non fire-retardant polyurethane foam 20-22kg/m³.

Test Conditions: The test was conducted within the required conditions of 15-30°C & 20-70%rh.

#### **RESULTS**

Source No.	Application No.	Application Time	Flaming Time Following Removal of Source	Smoke/ Smoulder	Result - Ignition/ Non-Ignition
1	1	20sec	00min 00sec	00min 16sec	PASS N/I
	2	20sec	00min 00sec	00min 17sec	PASS N/I

#### **COMMENTS**

SCHEDULE 5 PART 1 THE MATCH TEST BASED ON BS 5852: 1979 PART 1 THE MATCH TEST	APP 1.	APP 2.
After removal of the ignition source the cover fabric melted open to expose the underlying filling material. The cover and filling assembly immediately ignited. The rate of fire development was rapid and the test was terminated before the stipulated 120sec time period as it was unsafe to continue.	NO - PASS N/I	NO - PASS N/I
After removal of the ignition source the cover fabric melted open to expose the underlying filling material. The cover and filling assembly immediately ignited. Flames continued beyond the stipulated 120sec time period.	NO - PASS N/I	NO - PASS N/I
After removal of the ignition source the cover fabric ignited, flames spread across the surface of the cover, leaving behind an intact char. The cover continued to burn for greater than the stipulated 120sec time period.	NO - PASS N/I	NO - PASS N/I
After removal of the ignition source the cover ignited, the cover char split and the underlying filling material ignited, the cover and filling assembly continued to burn for greater than the stipulated 120sec time period.	NO - PASS N/I	NO - PASS N/I
All flames ceased within the permitted 120sec, the test assembly continued to smoulder for greater than the stipulated 15min time period.	NO - PASS N/I	NO - PASS N/I

## **CONCLUSION**

This fabric sample Ref: Passione 4193, passes the test specified in Schedule 5 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations 1988 - Amended 1989, 1993 and 2010.

Tested by: Ollie Baker

Reported by: Vanessa Mitchell

Approved by: Nathaly Da Silva

Operations Co-Ordinator

\*\*\*\*\*\* End of Report \*\*\*\*\*\*\*\*



